

ML.13.07	<b>TECHNICAL DATA SHEET</b>	
Released.01 Dated 16/10/18		

## **IDRACLEAN L453/2**

### *DETERGENT*

#### **APPLICATION**

---

**IDRACLEAN L453/2** is a specific detergent formulated to remove residues, stains, stubborn fouling and halos. It is used for cleaning hard surfaces such as: floors (marble, granite, ceramics ..) and walls. It is used for hard-to-clean surfaces, where ordinary detergents are usually not effective. It is used to remove residues of mortars and epoxy sealants.

#### **USE**

---

**IDRACLEAN L453/2** is supplied concentrated: it can therefore be diluted as needed and degree of dirt to be removed.

For stubborn dirt such as epoxy mortar residues, it is suggested to use the pure product leaving it to act on the dirt for about 10 minutes. After the action, remove everything with a cloth and rinse thoroughly with water. The application can be repeated if necessary, after complete drying of the previous application.

For the removal of halos and dirt from tiles instead it is recommended to dilute the product 1:5-1:10 with water before application as described above.

The application is done by brush or abrasive sponge.

In all cases it is suggested to do a compatibility test with the support to be cleaned by placing the product in a hidden area to verify that it does not also affect the surface.

ML.13.07	<b>TECHNICAL DATA SHEET</b>	
Released.01 Dated 16/10/18		

## PRODUCT CHARACTERISTICS

---

APPEARANCE	: Clear liquid free of suspended solids
SOLID CONTENT	: ca. 8,0%
pH	: ca. 8,5
STORAGE	: 12 months. 5 - 35°C. Protect against frost
NOTE	: Shake well before use

All information is given in good faith but without warranty and we cannot accept responsibility or liability for any damage.