

ML.13.07	<b>TECHNICAL DATA SHEET</b>	
Released.01 Dated 16/10/18		

## IDRAFIX MATT L227/4

### *MIXTURE OF RESINS IN AQUEOUS SOLUTION*

#### **APPLICATION**

---

**IDRAFIX MATT L227/4** is an aqueous dispersion of resins with characteristics of high resistance to hydrolysis and light, designed as a final finishing product for furnishing leathers. It gives the skin a degree of semi-gloss matte, excellent printability and natural hand that remains even after prolonged beating; a peculiar feature of this product is the excellent repolishability of the tips obtained by rubbing.

It is generally cross-linked with isocyanate in percentages varying from 5% to 10%, giving excellent results of resistance to dry and wet Veslic and maintaining unchanged hand and softness.

Cross-linked mixtures with isocyanate should be used within 6 - 8 hours.

**IDRAFIX MATT L227/4** suitably formulated for ready use.

Shake thoroughly before use

#### **PRODUCT CHARACTERISTICS**

---

APPEARANCE	: Translucent liquid
SOLID CONTENT	: ca. 17,0%
SPECIFIC GRAVITY	: 1,0 g/L
PHASE	: Aqueous
pH	: 8,0 - 10,0
STORAGE	: 12 months. 5 - 35°C. Protect from frost
NOTE	: Shake well before use

All information is given in good faith but without warranty and we cannot accept responsibility or liability for any damage.