

Mod. 04/B Ed 2 15.07.07	TECHNICAL DATA SHEET	
Pag. 1 di 1		
Released n° 0	Edition: 21 st February 2011 Released:	

IDRAFIX MATT L312/12

RESIN MIX IN WATERY SOLUTION

USE

IDRAFIX MATT L312/12 is an aqueous dispersion of resins with outstanding resistance to hydrolysis and to light, designed as finishing product for furniture leather with special physical properties.

It is used as a final fixative giving a grade of opaque balanced, excellent printability and natural hand that remains even after drumming prolonged.

It is generally crosslinked with isocyanate in percentages ranging from 5% to 10% giving excellent resistance to dry and wet VESLIC, while maintaining softness and hand.

The product crosslinked with isocyanate must be used within 6 to 8 hours.

IDRAFIX MATT L312/12 is appropriately formulated for rapid deployment.

Stir well before use.

PRODUCT CHARACTERISTICS

APPEARANCE	Milky fluid
SOLIDS	15 %. (approx)
TYPE	Mix of synthetic resins
SPECIFIC GRAVITY	1,00 g/cm ³
pH	8,0 - 9,0
PHASE	water
STORAGE	12 months. 5-35 °C. Keep from freezing
NOTE	Stir well before use

All information is given in good faith but without warranty and we cannot accept responsibility or liability for any damage.